



K1K2K3K4

1	30.1759.24	Casing-kit -RL26 +screws, Sst.	1				1
2	30.1764.51	Spring, 1,3x9,1x24 mm Sst.	1				25
3	10.3060.01	O-ring, 1,78x12,42 mm Ni 85	1	•			10
4	30.1763.31	Plug, M14x1 brass	1				10
5	30.1762.21	Shutter, complete	1	•			5
6	30.1708.20	Seat, 6mm Sst.+O-ring 1,78mm NBR85	1	•			10
7	30.0704.51	Piston, 3-4 mm Sst.	1	•			10
8	14.3511.00	Washer, 3,2x7x0,5 mm sst.	1	•			10
9	10.3165.00	O-ring, 2,62x2,84 mm Vi 70	1	•			10
10	10.4018.00	Back-up ring, 3,2x7,5x1,2 mm	1	•			10
11	30.1700.35	Central housing -RL26, 1/4F Bsp brass	1				5
12	30.0675.84	Stop pin, 8x7,1mm PA	1				10



K1	30.1766.24	Repair kit -RL25 weep.LP, 7x1pcs.	1
----	------------	-----------------------------------	---

(1) 30.1782.00

K1K2K3K4

13	30.1704.84	Trigger -RL26, PA black	1				10
14	30.0509.31	Parallel pin, 5x24,5 mm brass	1				10
15	16.3075.51	S/tapping scr. 3,5x18 mm sst.	7				10
16	30.2599.84	Safety latch, PA green	1				10
17	30.0706.56	Tube, 1/8Bsp MM Sst.	1				10
18	30.1512.31	Coupl., 1/8F-3/8F Bsp brass	1				5
19	30.1731.56	Tube, 1/8Bsp MM 116 mm Sst. (1)	1				5
20	30.1733.31	Adapt., M10x1F-1/8F Bsp brass (1)	1				5
21	30.2019.31	Coupl., 3/8F Bsp brass (1)	1				5
22	10.4010.01	Back-up ring, 10,2x13,9x1,2mm (1)	2				50
23	30.1732.31	Pin -SW, M10x1 M (1)	1				5
24	10.3129.50	O-ring, 2,5x9,5 mm Vi 70 (1)	1				10